

1. Product and Company Identification

- 1.1 **PRODUCT NAME:** Traxx Primer 1050
- 1.2 **USE OF PRODUCT** General purpose primer for Traxx and Chevaline Colourcure finishes on most porous building material surfaces, ferrous and some non-ferrous metals.
- 1.3 **SUPPLIER:** Equus Industries Ltd
Sheffield Street
Riverlands Industrial Estate
Blenheim, Marlborough, New Zealand
Telephone: +64 3 578 0214
Fax: +64 3 578 0919
E-mail: admin@equus.co.nz
- 1.4 **EMERGENCY CONTACT:** **National Poison Centre Telephone: 0800 764 766**
- 1.5 **DATE OF PREPARATION:** 26 April 2024

2. Hazards Identification

- 2.1 **Statement of Hazardous Nature:**
Classified as hazardous according to New Zealand Hazardous Substances (Minimum degrees of hazard) Regulations 2020.
- 2.2 **HSNO GROUP STANDARD:**
HSR002699 – Surface Coatings and Colourants (Flammable, Carcinogenic)2020
- 2.3 **GHS Classification:**

Flammable Liquids	Category 3
Skin corrosion / irritation.	Category 2
Skin sensitisation	Category 1
Serious eye damage / irritation	Category 2A
Acute toxicity / inhalation	Category 4
Respiratory sensitisation	Category 1
STOT – SE	Category 3
Carcinogenicity	Category 2
STOT – RE	Category 2
Aquatic Toxicity (chronic)	Category 3



Signal Word: DANGER

2.5 Hazard Statements:

H226	Flammable liquid and vapour
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer
H373	May cause damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

2.6 Prevention Statements:

P102	Keep out of reach of children.
P103	Read label before use.
P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat/sparks/open flames/hot surfaces No smoking
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment
P241	Use explosion-proof electrical/ventilating/lighting
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge
P260	Do not breathe dust/fume/gas/mist/vapours/spray
P261	Avoid breathing dust/fume/gas/mist/vapours/spray
P264	Wash hands, face and all exposed skin thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P272	Contaminated work clothing should not be allowed out of the workplace.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection
P285	In case of inadequate ventilation wear respiratory protection

2.7 Response Statements:

P101	If medical advice is needed, have product container or label at hand.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P303 + P361 + P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304 + P340	IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P308 + P313	IF exposed or concerned: Get medical advice/ attention
P314	Get medical advice/attention if you feel unwell.
P332 + P313	If skin irritation occurs: Get medical advice/ attention.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
P342 + P311	If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.
P312	Call a POISON CENTER or doctor/physician if you feel unwell.
P362	Take off contaminated clothing and wash before re-use.
P363	Wash contaminated clothing before reuse.
P370 + P378	In case of fire: Use carbon dioxide, dry chemical or foam.

2.8 Storage Statements:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
 P403 + P235 Store in a well-ventilated place. Keep cool.
 P405 Store locked up.

2.9 Disposal Statement:

P501 Do not let this product enter the environment. Do not dispose of in waterways or sewers. Dispose of this material and its container as hazardous waste, via a licensed facility. See local council for disposal/recycling information.

3. Composition/Information on Ingredients

CAS NO.	COMPONENT	Proportion (% W/W)
67815-87-6	Prepolymer based on aromatic polyisocyanate	28.5
9016-87-9	diphenylmethane-diisocyanate, isomers and homologues	17
101-68-8	Diphenylmethane-4,4- diisocyanate	2
5873-54-1	Diphenylmethane – 2,4- diisocyanate	2
1330-20-7	Xylene	50
Balance of ingredients: Nonhazardous, or below the hazard threshold		

4. First Aid Measures

4.1 After Inhalation:

If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. If required, artificial respiration or administration of oxygen can be performed by trained personnel. If symptoms persist, seek medical attention.

4.2 After Skin Contact:

Remove/take off all contaminated clothing. Wash area of contact thoroughly with plenty of soap and water. If irritation, rash or other disorders develop, seek medical attention immediately. Wash contaminated clothing before re-use.

4.3 After Eye Contact:

Rinse cautiously with water for at least 15 minutes while holding eye lids apart. Remove contact lenses if present and easy to do. Continue rinsing. If irritation persists, seek medical advice/attention.

4.4 After Ingestion:

Immediately call the Poison Centre or Doctor/Physician.

4.5 General:

Get immediate medical attention for any significant over exposure.

4.6 Advice to Doctor:

Treat symptomatically.

5. Fire Fighting Measures

5.1 Suitable Extinguishing Media:

If water fog is ineffective, use carbon dioxide, dry chemical or foam.

5.2 Protective Equipment:

Use accepted firefighting techniques. Wear full firefighting protective clothing, including self-contained breathing apparatus (SCBA). Water may be used to cool containers to minimise pressure build-up.

5.3 Specific Hazards:

Product may ignite if heated in excess of its flashpoint. Closed containers may burst when exposed to extreme heat. Empty containers may contain ignitable vapours. Vapours may travel to sources of ignition and flash back.

5.4 Combustion Products:

Carbon monoxide and carbon dioxide can form. Smoke, fumes. Hydrocyanic acid and nitrogen oxides can form.

5.5 Fire and Explosion Conditions:

Product may ignite if heated in excess of its flashpoint.
Vapours may travel to source of ignition and flashback.
Closed container may burst when exposed to extreme heat.
Containers may contain ignitable vapours.

5.6 Additional Information:

Flashpoint = 29°C (closed cup) Hazchem Code 3[Y].

6. Accidental Release Measures

6.1 Preliminary Action and Precautions:

6.1.1 Eliminate very possible source of ignition.

6.1.2 Evacuate all personnel immediately and ventilate area.

6.1.3 Avoid breathing vapour and contact with skin, eyes and clothing.

6.1.4 Wear recommended personal protective equipment.

6.1.5 Shut off leaks if possible without risk.

6.1.6 Dike in the spilled product as much as possible with inert material.

6.1.7 Prevent entry of product into sewers, storm water drains and open bodies of water.

6.1.8 Clean up all spills as soon as possible, using an inert absorbed material and dispose of as hazardous waste.

7. Handling and Storage

7.1 Handling:

7.1.1 Prevent inhalation of vapour, ingestion and contact with skin, eyes and clothing.

7.1.2 Keep container closed when not in use. Precautions also apply to emptied containers.

7.1.3 Change soiled work clothing frequently.

7.1.4 Clean hands thoroughly after handling.

7.1.5 Do not smoke, weld, generate sparks, or use flame near container.

- 7.1.6 To prevent generation of static discharges, use bonding/grounding connection when pouring liquid.
- 7.1.7 Extinguish all ignition sources including pilot lights, and do not use non-explosion proof motors and electrical equipment until vapours dissipate.
- 7.2 **Storage:**
 - 7.2.1 Store under dry cool warehouse conditions.
 - 7.2.2 Store away from sources of ignition, (i.e. sparks, open flames, heat etc)
 - 7.2.3 Store away from strong acids, strong bases, amines, water or moisture, and alcohols.
 - 7.2.4 Keep containers tightly closed at all times.

8. Exposure Controls and Personal Protection Equipment

8.1 Exposure Limits:

CHEMICAL NAME	CAS NUMBER	REGULATION	LIMIT
All Isocyanates	-	WES – TWA WES – STEL	0.02 mg/m ³ 0.07 mg/m ³
Xylene	1330-20-7	WES – TWA	50 ppm 217 mg/m ³

8.2 Exposure Controls:

8.2.1 Exposure Controls in the Work Place:

Use only in well ventilated areas. Provide maximum ventilation in enclosed areas. Use local exhaust when the general ventilation is inadequate.

8.2.2 Personal Protection Equipment

Respiratory Protection – Wear appropriate, properly fitted NIOSH/MSHA, approved respirator when airborne contaminant level(s) are expected to exceed exposure limits indicated on the SDS. Select positive pressure supplied air respirator for isocyanates, (TC 19c or equivalent).

Hand Protection – Use suitable impervious nitrile or neoprene gloves and protective apparel to reduce exposure.

Eye Protection – Wear appropriate eye protection. Wear chemical safety goggles and/or face shield to prevent eye contact. Do not wear contact lenses. Do not touch eyes with contaminated body parts or materials. Have eye washing facilities readily available.

Skin/Body Protection - Wear suitable protective clothing, e.g. long sleeved cotton overalls.

Protective Measures - Use professional judgment in the selection, care, and use.

9. Physical and Chemical Properties

9.1 General Information:

Physical State/Form	Liquid
Colour	Light Brown
Odour	Hydrocarbon
pH	-
Flash Point	29°C (closed cup)
Water Solubility/Miscibility	0.085 kg/m ³

Specific Gravity	0.99
% Volatile Weight	50
VOC (less water and exempt Solvent)	495 g/l

10. Stability and Reaction

10.1 General Information:

This material is stable when properly handled and stored.

10.2 Conditions to Avoid:

High temperatures, open flames, sparks.

10.3 Material to Avoid:

Strong acids, strong bases, amines, water or moisture and alcohols.

10.4 Hazardous Decomposition Products:

None expected when material properly handled and stored. For thermal decomposition see Section 5.

10.5 Hazardous Polymerisation:

Will not occur under normal conditions.

11. Toxicological Information

11.1 Health Effects/Symptoms of Exposure:

Vapour and/or mist may irritate nose and throat. Leave area to breathe fresh air. Avoid further over exposure. If symptoms persist, seek medical attention.

Xylene	CAS No. 1330-20-7
Oral (Mouse)	1,590 mg/kg
Inhalation LC50 (Rat)	27.6 mg/kg

Polymer based on Aromatic Isocyanate	CAS No. 67815-87-6
Oral LD50 (Rat)	> = 5,000 mg/kg

4,4'-diiphenylmethane-diisocyanate, isomers, homologues	CAS No. 9016-87-9
Oral LD50 (Rat)	9,200 mg/kg
Inhalation LC50 (Rat)	179 mg/m ³

11.3 Skin Contact:

May cause sensitization resulting in irritation, itching and redness.

11.4 Eye Contact:

Vapours and/or mist may cause eye irritation.

11.5 Ingestion:

May cause irritation to the mouth, throat and stomach. May cause gastrointestinal irritation, nausea and vomiting.

11.6 Inhalation:

May cause drowsiness, weakness, and fatigue. Vapour and/or mist may irritate nose and throat. May cause moderate irritation to the respiratory system. May cause allergic respiratory sensitization.

11.7 Chronic Effects:

Unless suitable engineering controls and/or personal protective equipment is used:

- Repeated over-exposure to vapour may lead to asthma and sensitization or damage to the respiratory system.
- Repeated unprotected physical contact with the material may cause defatting of the skin leaving it vulnerable to irritation, dermatitis and/or sensitization.
- Prolonged over exposure to vapour and/or unprotected physical contact may lead to internal organ sensitization and/or damage. The Central Nervous System may also be affected.

12. Ecological Information

12.1 Environment Protection:

Prevent from entering drains, sewers and waterways.

May cause long lasting harmful effects to aquatic life.

12.3 Persistence and degradability:

Data not available.

12.4 Bioaccumulative Potential:

Data not available.

13. Disposal Consideration

13.1 Disposal Methods

Subject to hazardous waste treatment, storage and disposal requirements. Recycle or incinerate waste at approved facility or dispose of in compliance with national/regional/local, waste disposal regulations. DO NOT EMPTY INTO DRAINS, SEWERS OR WATERWAYS.

14. Transport Information

14.1 Regulated under NZS 5433 for land transport.

UN Number	1263
Proper Shipping Name	Paint Related
Class	3
Packing Group	III
Hazchem Code	3Y

15. Regulatory Information

15.1 HSNO Approval:

Approval Code	HSR 002669
HSNO Group Standard	Surface Coatings and Colourants (Flammable, Carcinogenic)2020

16. Other Information

16.1 Abbreviations/Terminology:

HSNO	Hazardous substances and New Organisms Act
CAS	Chemical Abstract Service
ACGIH	American Conference of Governmental Industrial Hygienists
LD50, LC50	Lethal dose/Lethal Concentration – Dose or concentration required to produce the specified effect in 50% of the sample studied.

WES	Workplace Exposure Standard (NZ Department of Business, Innovation and Employment)
TWA	Time weighted average exposure level designed to protect from the effects of long-term exposure.
STEL	Short-term Exposure Level (15 minutes)
VOC	Volatile Organic Compound

16.3 Issue Information:

Date of Preparation:	26 April 2024
Reasons:	Update and format change to GHS only
Replaces:	29 May 2019

16.4 The information contained in this Data Sheet relates only to the specific material identified. Equus Industries Ltd believes the information to be accurate and reliable as at the date of this Data Sheet. No Warranty, Guarantee or representation is expressed or implied by the Company as to the absolute correctness or completeness of any representation contained in this Data and assumes no legal responsibility in connection therewith. It can not be assumed that all acceptable safety measures are contained in this Data Sheet, or that additional measures may not be required under particular or exceptional circumstances or conditions.