

# Adjustable tile support

## Description:

De Boer adjustable tile supports are made of tough polypropylene and resist all types of weather conditions. The supports are durable and UV-resistant.

The supports have a base of 300cm<sup>2</sup> and an outer diameter of 21.5cm. One support has a load capacity of 1000kg.

The supports create open joints of 3mm in between tiles. The height of the supports is adjustable from 5cm to 24cm.

## Basic uses:

To raise concrete tiles from the waterproofing membrane surface.

To raise wooden decking from the waterproofing membrane surface.

To allow water to drain quickly through the open joints and under the tiles and wooden decking to the roof outlet.

These adjustable tile supports are compatible to all De Boer waterproofing cap sheets.

Tiles and decking can be lifted in case of modification or inspection of the waterproofing is required.

## Available sizes:

3cm to 5cm - 5cm to 9cm - 9cm to 13cm - 11 to 15cm - 15cm to 19 cm

The directives in this documentation are the result of our lab-tests and trials and our experience, and they are being provided in good faith. As we have no control on the application modalities we can never be held responsible for the results and for damage caused by wrong or inappropriate use.



Equus Industries Ltd  
PO Box 601  
Blenheim  
Phone: 03 578 0214  
Email: [admin@equus.nz](mailto:admin@equus.nz)  
Website: [www.equus.nz](http://www.equus.nz)  
May 2012